

JP MODEL

WEBBING SLINGS



- These slings are made of high strength materials as per norm EN 1492-1.
- The slings strips are strengthened, which gives them greater resistance and extends the life of the sling.
- Flat slings, according to European standards, are suitable for use and storage facilities in the temperature range from [-40 ° C to 100 °].


Note:

Safety factor 7:1.

MAX WORKING LOAD (M.W.L.) Kg.

MODEL	COD. COLOUR NORM CEN	WIDTH/ THICKNESS	1 SLING								2 SLINGS		3-4 SLINGS	
			DIRECT SHOT	HANGED	TITL ANGLE β			TITL ANGLE β		TITL ANGLE β				
					0-7°	7-45°	45-60°	0-45°	45-60°	0-45°	45-60°			
			1.0	0.8	2.0	1.4	1.0	1.4	1.0	2.1	1.5			
JP-30	Violeta	30/7	1.000	800	2.000	1.400	1.000	1.400	1.000	2.100	1.500			
JP-60	Verde	60/7	2.000	1.600	4.000	2.800	2.000	2.800	2.000	4.200	3.000			
JP-90	Amarillo	90/7	3.000	2.400	6.000	4.200	3.000	4.200	3.000	6.300	4.500			
JP-120	Gris	120/7	4.000	3.200	8.000	5.600	4.000	5.600	4.000	8.400	6.000			
JP-150	Rojo	150/7	5.000	4.000	10.000	7.000	5.000	7.000	5.000	10.500	7.500			
JP-180	Marrón	180/7	6.000	4.800	12.000	8.400	6.000	8.400	6.000	12.600	9.000			
JP-240	Azul	240/7	8.000	6.400	16.000	11.200	8.000	11.200	8.000	16.800	12.000			
JP-300	Naranja	300/7	10.000	8.000	20.000	14.000	10.000	14.000	10.000	21.000	15.000			


RECOMMENDED ACCESSORIES



POLYESTER CONNECTOR
Pag. 75



MASTERLINK
Pag. 74



SHACKLES
Pag. 94