

# JR MODEL

## ROUND ENDLESS POLYESTER SLINGS

- These slings are made of high strength materials as per EN 1492-1 standards.
- Round slings, according to European standards, are suitable for use and storage facilities in the temperature range from [-40 °C to 100 °C].

**Note:**


Safety factor 7:1.



CARGA MÁXIMA DE UTILIZACIÓN (C.M.U.) KGS.

MODEL	COD. COLOUR CEN NORM	WIDTH	1 SLING										2 SLINGS		3-4 SLINGS	
			DIRECT SHOT	HANGED	TITL ANGLE $\beta$			TITL ANGLE $\beta$		TITL ANGLE $\beta$						
					0-7°	7-45°	45-60°	0-45°	45-60°	0-45°	45-60°					
			1.0	0.8	2.0	1.4	1.0	1.4	1.0	2.1	1.5					
JR-40	Violet	40	1.000	800	2.000	1.400	1.000	1.400	1.000	2.100	1.500					
JR-50	Green	50	2.000	1.600	4.000	2.800	2.000	2.800	2.000	4.200	3.000					
JR-60	Yellow	60	3.000	2.400	6.000	4.200	3.000	4.200	3.000	6.300	4.500					
JR-70	Gray	70	4.000	3.200	8.000	5.600	4.000	5.600	4.000	8.400	6.000					
JR-75	Red	75	5.000	4.000	10.000	7.000	5.000	7.000	5.000	10.500	7.500					
JR-80	Brown	80	6.000	4.800	12.000	8.400	6.000	8.400	6.000	12.600	9.000					
JR-90	Blue	90	8.000	6.400	16.000	11.200	8.000	11.200	8.000	16.800	12.000					
JR-100	Orange	10	10.000	8.000	20.000	14.000	10.000	14.000	10.000	21.000	15.000					


RECOMMENDED ACCESSORIES



POLYESTER CONNECTOR  
Pag. 75



MASTER LINK  
Pag. 74



SHACKLES  
Pag. 94