

SPTG AND SATC MODELS

GRADE 80 LASHING CHAINS SYSTEM



Chain sling systems are designed for transporting heavy loads by any means: road, rail, sea and air. The tensioners come with shorteners and a safety lock. To prevent vibrations during transport loosen the chain.

Características:

- Complies with the EN 12195-3 standard.
- Chain tensioners with safety device.
- Chain length by choice, made to measure.
- Can be supplied with hooks with latch and chain shorteners.
- Identification plates indicating capacity and standard tension force.
- Grade 80 chains and accessories.



MODEL	MEASUREMENTS CHAIN (MM.)	MOORING CAPACITY: (LC.) KN	STANDARD TENSION FORCE (STF.) DAN	BREAK FORCE (BF.) KN
SPTG1000	8	40	2000	80,4
SPTG2000	10	63	3150	126
SPTG3000	13	100	3500	212
SPTG4000	16	160	3500	340
SATC1000	8	40	2000	80,4
SATC2000	10	63	3150	126
SATC3000	13	100	3500	212
SATC4000	16	160	3500	340



EYEBOLT RATCHET TENSIONER ATC MODEL
Pag. 52



RATCHET TENSIONER WITH HOOKS PTG MODEL
Pag. 52



HOOK WITH LATCH DIRECT CONNECTION G.80 MODEL
Pag. 75



SHORT HOOK WITH DIRECT CONNECTION LATCH G.80 MODEL
Pag. 76