

680 AC SERIES

CORROSION-RESISTANT HAND CHAIN HOISTS

The 680AC series chain hoists are designed and manufactured in accordance with the requirements of ISO12944, with the highest anticorrosion grade, up to C5-m.

This product is suitable for use in marine environments and places with high salinity.





Stainless steel latches, nuts and identification plate

Studs, rollers, nails and chain end with corrosion protection

environments

Ideal bronze bearing for marine


Protective cover




JAGUAR differential pulleys are not designed for lifting people and must not be used for this purpose.

OPTIONAL:

· Rustproof load chain







High strength steel chain with Dacromet finish for increased durability against corrosion

CODE	CAPACITY (kg)	No. LINKS	FORCE (N.)	WEIGHT WITH 3 m (kg)	MAX LIFTING WEIGHT (kg)	HOOK OPENING (mm)	DIMENSIONS			
							Α	В	С	н
AFKAC2000	500	1	240	9	1,5	23	148	132	23	345
AFKAC3000	1.000	1	250	12	1,69	26	172	151	26	376
AFKAC5000	2.000	1	335	20	2,54	34	210	175	34	470
AFKAC6000	3.000	1	372	32	3,14	39	255	255	39	580
AFKAC8000	5.000	2	380	43	5,34	41	280	280	41	690
AFKAC11000	10.000	4	385	81	9,74	50	385	385	50	780

RECOMMENDED ACCESSORIES



