


## PCGM MODEL (SHORT) FOLDABLE SWIVEL EYEBOLTS




**Features:**

- Safety coefficient of 4:1
- Screw quality 10.9.
- No reduction in load capacity at the angles you can work at.
- Manufactured according to EN-1677-1 standard

CODE	METRICS mm	WORKING LOAD C.M.T. / TON	L	A	B	C	D	F	K	M	H	S	TIGHTENING TORQUE Nm	WEIGHT Kg
PCGM81205	M8	0.5	12	48.5	37	76	14	103.5	49.5	8	40	10.5	30	0.8
PCGM101607	M10	0.7	16	48.5	37	76	14	103.5	49.5	10	40	10.5	60	0.8
PCGM121810	M12	1	18	48.5	37	76	14	103.5	49.5	12	40	10.5	100	0.8
PCGM142115	M14	1.5	21	48.5	37	76	11	103.5	49.5	14	40	10.5	120	0.8
PCGM162420	M16	2	24	73	37	76	14	103.5	49.5	16	40	10.5	150	0.8
PCGM204030	M20	3	40	73	54	106	20	151	77	20	54	14.5	250	2
PCGM244045	M24	4.5	40	98.5	54	106	20	151	77	24	54	14.5	400	2.5
PCGM304573	M30	7.3	45	98.5	74	149	30	206.5	103.5	30	73	22.5	500	5.5
PCGM335080	M33	8	50	98.5	74	149	30	206.5	103.5	33	73	22.5	800	5.5
PCGM3654100	M36	10	54	98.5	74	149	30	206.5	103.5	36	73	22.5	1000	5.5
PCGM3958100	M39	10	58	98.5	74	149	30	206.5	103.5	39	73	22.5	1200	6
PCGM4263125	M42	12.5	63	98.5	74	149	30	206.5	103.5	42	73	22.5	1500	6
PCGM4563150	M45	15	63	117.5	74	149	30	206.5	103.5	45	73	22.5	1800	6
PCGM4868200	M48	20	68	117.5	93	183	36	255	122	48	93	27.5	2000	11.5
PCGM5268200	M52	20	68	117.5	93	183	36	255	122	52	93	27.5	2000	12
PCGM5678250	M56	25	78	117.5	93	183	36	255	122	56	93	27.5	2100	12
PCGM6490320	M64	32	90	186	93	183	36	255	122	64	93	27.5	2200	13

**LIFTING METHOD**



**NUMBER OF LINKS**

1    1    2    2    2    2    3-4    3+4    2    3+4

**INCLINATION ANGLE**


0°    90°    0°    90°    0° - 45°    45° - 60°    0° - 45°    45° - 60°    ASYMMETRIC    ASYMMETRIC

CODE	METRICS mm	LOAD CAPACITY Kg									
PCGM81205	M8	500	500	1.000	1.000	700	500	1.100	800	500	500
PCGM101607	M10	700	700	1.400	1.400	1.000	700	1.500	1.100	700	700
PCGM121810	M12	1.000	1.000	2.000	2.000	1.400	1.000	2.100	1.500	1.000	1.000
PCGM142115	M14	1.500	1.500	3.000	3.000	2.100	1.500	3.150	2.300	1.500	1.500
PCGM162420	M16	2.000	2.000	4.000	4.000	2.800	2.000	4.200	3.150	2.000	2.000
PCGM204030	M20	3.000	3.000	6.000	6.000	4.200	3.000	6.300	4.500	3.000	3.000
PCGM244045	M24	4.500	4.500	9.000	9.000	6.300	4.500	9.450	6.800	4.500	4.500
PCGM304573	M30	7.300	7.300	14.600	14.600	10.200	7.300	15.300	11.000	7.300	7.300
PCGM335080	M33	8.000	8.000	16.000	16.000	11.200	8.000	16.800	12.000	8.000	8.000
PCGM3654100	M36	10.000	10.000	20.000	20.000	14.000	10.000	21.000	15.000	10.000	10.000
PCGM3958100	M39	10.000	10.000	20.000	20.000	14.000	10.000	21.000	15.000	10.000	10.000
PCGM4263125	M42	12.500	12.500	25.000	25.000	17.500	12.500	26.300	18.800	12.500	12.500
PCGM4563150	M45	15.000	15.000	30.000	30.000	21.000	15.000	31.500	22.500	15.000	15.000
PCGM4868200	M48	20.000	20.000	40.000	40.000	28.000	20.000	42.000	30.000	20.000	20.000
PCGM5268200	M52	20.000	20.000	40.000	40.000	28.000	20.000	42.000	30.000	20.000	20.000
PCGM5678250	M56	25.000	25.000	50.000	50.000	35.000	25.000	53.000	37.500	25.000	25.000
PCGM6490320	M64	32.000	32.000	64.000	64.000	45.000	32.000	67.000	48.000	32.000	32.000


**RECOMMENDED ACCESSORIES**



'DOL' SLING  
Pag. 84



FLAT SLINGS  
Pag. 94



ROUND SLINGS  
Pag. 95