


PHCMG MODEL KEY SWIVEL EYEBOLTS



Features:

- Auto adjustment in the direction of load pulling.
- Key locking system.
- According to EN-1677-1, Factor 4: 1.
- Screw quality 12.9.
- 360° rotation

Note: Allen key included to facilitate the tightening of the eyebolt.

CODE	METRICS mm	WEIGHT Kg	C.M.T. / TON		TIGHTENING TORQUE NM	A	B	C	D	E	F
			Z	X							
PHCMG08	M8	0.11	0.8	0.3	30	39	26	46	12	25	8
PHCMG10	M10	0.12	1	0.4	60	39	26	46	12	25	8
PHCMG12	M12	0.2	2	0.75	100	44	32	54	18	34	10
PHCMG16	M16	0.35	4	1.5	150	52	37	64	24	36	15
PHCMG20	M20	0.66	6	2.3	250	64	44	78	30	47	21
PHCMG24	M24	11	8	3.2	400	74	51	92	36	53	20
PHCMG30	M30	2.07	12	4.5	500	92	65	118	45	68	24
PHCMG36	M36	4.0	16	7	700	105	76	136	57	82	30

LIFTING METHOD										
NUMBER OF LINKS	1	1	2	2	2	2	3+4	3+4	2	3+4
INCLINATION ANGLE	0°	90°	0°	90°	0° - 45°	45° - 60°	0° - 45°	45° - 60°	ASYMMETRIC	ASYMMETRIC

CODE	METRICS mm	LOAD CAPACITY Kg									
PHCMG08	M8	800									
PHCMG10	M10	1.000	400	2.000	800	560	400	800	600	400	400
PHCMG12	M12	2.000	750	4.000	1.500	1.000	750	1.500	1.100	750	750
PHCMG16	M16	4.000	1.500	4.000	3.000	2.100	1.500	3.100	2.200	1.500	1.500
PHCMG20	M20	6.000	2.300	12.000	4.600	3.200	2.300	4.800	3.400	2.300	2.300
PHCMG24	M24	8.000	3.200	16.000	6.400	4.500	3.200	6.700	4.800	3.200	3.200
PHCMG30	M30	12.000	4.500	24.000	9.000	6.300	4.500	9.400	6.700	4.500	4.500
PHCMG36	M36	16.000	7.000	32.000	14.000	9.800	7.000	14.700	10.500	7.000	7.000

RECOMMENDED ACCESSORIES



DOL SLING
 Pag. 84



FLAT SLINGS
 Pag. 94



ROUND SLINGS
 Pag. 95