STC MODEL

RATCHET STRAPS LASHING SYSTEMS



Belt lashing systems are designed for the transport of heavy loads by any means, road, rail, sea and air.

It is provided with a ratchet to tighten and fasten the load, preventing vibrations during transport from loosening the belt.

Features

- · Complies with the EN 12195-2 standard.
- Double labelling with specification and sewn and laminated user manual.
- · Jaguar badge and fastening capacity engraving.
- · Galvanized anti-corrosion finishes.
- All slings are provided with CE Declaration of conformity with individual serial number









ERGURAICHETSTRAPSLASHING SYSTEMS				
CODE	LC (LASHING CAPACITY)/LENGTH	ноок	WIDTH	
STCE59U	LC 2500/5000 daN X 9M	U	50MM	
STCE59J	LC 2500/5000 daN X 9M	J	50MM	

	RATCHET STRAPS LASHING SYSTEMS		
CODE	LC (LASHING CAPACITY)/LENGTH	ноок	WIDTH
STC26U	LC 1000/2000 daN X 6M	U	35MM
STC49U	LC 2000/4000 daN X 9M	U	50MM
STC4105U	LC 2000/4000 daN X 10.5M	U	50MM
STC4135U	LC 2000/4000 daN X 13.5M	U	50MM
STC59U	LC 2500/5000 daN X 9M	U	50MM
STC510U	LC 2500/5000 daN X 10M	U	50MM
STC085J	LC 800/1600 daN X 5M	J	25MM
STC26J	LC 1000/2000 daN X 6M	J	35MM
STC49J	LC 2000/4000 daN X 9M	J	50MM
STC4105J	LC 2000/4000 daN X 10.5M	J	50MM
STC4135J	LC 2000/4000 daN X 13.5M	J	50MM
STC59J	LC 2500/5000 daN X 9M	J	50MM
STC510J	LC 2500/5000 daN X 10M	J	50MM

OPEN POLYESTER SLING PROTECTOR		
CODE	DIMENSIONS	
PEPEN50	50MM	

CLOSED POLYESTER SLING PROTECTOR		
CODE	DIMENSIONS	
PEPB50	50MM	

RECOMMENDED ACCESSORIES







Pag. 99